

FEATURES:

- 1,000 ~ 20,000 VDC Rated Models
- Up to 0.5000 μf Capacitance
- $\pm 2 \sim 20\%$ Tolerance Options
- -55 to 85°C (full rated voltage)
- Insulation Resistane of 25 - 50k ΩF
- $<0.6\%$ Dissipation Factor @ 1,000Hz
- Tested 150% of Rated Voltage (1 min)
- ISO 9001:2015 Qualified Processes
- Tested to MIL-STD-202
- ROHS Compliance Upon Request



1 kV MODELS			
MODEL	(μf)	DIA	LENGTH
60x01202	0.0020	0.530	1-3/16
60x01502	0.0050	0.530	1-3/16
60x01103	0.0100	0.530	1-3/16
60x01203	0.0200	0.530	1-3/16
60x01503	0.0500	0.530	1-9/16
60x01104	0.1000	0.690	2-1/4
60x01254	0.2500	0.840	2-1/4
60x01504	0.5000	1.060	2-1/4

2 kV MODELS			
MODEL	(μf)	DIA	LENGTH
60x02202	0.0020	0.530	1-3/16
60x02502	0.0050	0.530	1-3/16
60x02103	0.0100	0.530	1-3/16
60x02203	0.0200	0.530	1-9/16
60x02503	0.0500	0.690	1-3/4
60x02104	0.1000	0.690	2-1/4
60x02254	0.2500	1.060	2-3/8
60x02504	0.5000	1.310	2-3/4

3 kV MODELS			
MODEL	(μf)	DIA	LENGTH
60x03202	0.0020	0.530	1-3/16
60x03502	0.0050	0.530	1-3/16
60x03103	0.0100	0.530	1-9/16
60x03203	0.0200	0.690	1-3/4
60x03503	0.0500	0.690	2-1/4
60x03104	0.1000	0.840	2-1/4
60x03254	0.2500	1.060	2-3/8
60x03504	0.5000	1.310	2-3/4

5 kV MODELS			
MODEL	(μf)	DIA	LENGTH
60x05102	0.0010	0.530	1-9/16
60x05202	0.0020	0.530	1-9/16
60x05502	0.0050	0.530	1-9/16
60x05103	0.0100	0.690	1-3/4
60x05203	0.0200	0.690	2-1/4
60x05503	0.0500	0.840	2-1/4
60x05104	0.1000	1.060	2-1/4
60x05254	0.2500	1.310	2-3/4

7.5 kV MODELS			
MODEL	(μf)	DIA	LENGTH
60-08102	0.0010	0.530	1-9/16
60-08202	0.0020	0.530	1-9/16
60-08502	0.0050	0.690	1-3/4
60-08103	0.0100	0.690	2-1/4
60-08203	0.0200	0.840	2-1/4
60-08503	0.0500	1.310	2-3/4
60-08104	0.1000	1.310	2,3/4

10 kV MODELS			
MODEL	(μf)	DIA	LENGTH
60x10102	0.0010	0.530	1-9/16
60x10202	0.0020	0.530	1-9/16
60x10502	0.0050	0.690	1-3/4
60x10103	0.0100	0.840	2-1/4
60x10203	0.0200	1.060	2-1/4
60x10503	0.0500	1.310	2-3/4
60x10104	0.1000	1.750	4-11/32

15 kV MODELS			
MODEL	(μf)	DIA	LENGTH
60x15501	0.0005	0.690	2-1/4
60x15102	0.0010	0.690	2-1/4
60x15202	0.0020	0.840	2-1/4
60x15502	0.0050	0.840	2-1/4
60x15103	0.0100	1.060	2-1/4
60x15203	0.0200	1.310	2-3/4
60x15503	0.0500	1.750	4-11/32

20 kV MODELS			
MODEL	(μf)	DIA	LENGTH
60x20501	0.0005	0.690	2-1/4
60x20102	0.0010	0.690	2-1/4
60x20202	0.0020	0.840	2-1/4
60x20502	0.0050	1.060	2-3/4
60x20103	0.0100	1.310	2-3/4
60x20203	0.0200	1.750	4-11/32

To complete the part number,
replace x with one of the the following:

x = Tolerance
 J = $\pm 5\%$
 K = $\pm 10\%$
 V = $+20/-10\%$
 M = $\pm 20\%$